

Line of vertically fixed Eurobord extruded aluminium cladding behind (shown dashed)

Flashclad extruded aluminium 2 Part Jamb

150mm min. to permanent paving or 225mm min. to unpaved ground to clause 9.1.3 of E2/AS1

Flashclad extruded aluminium Slimline Sill with End Cap (shown dashed)

NOTE:
Sill provides full joinery support (wanz bar not required)

Bottom of the Eurobord cladding to finish in line with the bottom of Flashclad aluminium Sill End Cap

Finished ground level

NOTE:
Aluminium joinery installed with flashing tape and air seal over PEF backing rod as per NZBC E2/AS1

Flashclad aluminium Mitre Soaker supplied by Flashclad installed by Builder

10mm gap

H3.1 packer supplied and installed by Flashclad

75 x 6mm hot dip galvanised Ramset AnkaScrews at 600mm crs. supplied and installed by Flashclad

25mm from the outside face of the framing (for building wrap detailing) or 25mm from the outside face of the Rigid Air Barrier to the back of the aluminium window or door frame



Flashclad
CLADDING FOR LIFE

SILL - DOOR OR WINDOW AT FLOOR LEVEL

Original Scale 1:2
Revision - 20 October 2015

Eurobord
VERTICAL