

Line of vertically fixed Euro-rib
extruded aluminium cladding
behind (shown dashed)

Flashclad extruded aluminium
2 Part Jamb

NOTE:
Aluminium joinery installed with
flashing tape and air seal over
PEF backing rod as per
NZBC E2/AS1

Flashclad aluminium Mitre
Soaker supplied by Flashclad
installed by Builder

10mm gap

150mm min. to permanent paving or 225mm min.
to unpaved ground to clause 9.1.3 of E2/AS1

Flashclad extruded aluminium
Metro Sill with End Cap
(shown dashed)

NOTE:
Sill provides full joinery support
(wanz bar not required)

Bottom of the Eurobord cladding to
finish in line with the bottom of
Flashclad aluminium Sill End Cap

Finished
ground level

H3.1 packer supplied and
installed by Flashclad

75 x 6mm hot dip galvanised
Ramset AnkaScrews at 600mm
crs. supplied and installed by
Flashclad

25mm from the outside face of the
framing (for building wrap detailing)
or 25mm from the outside face of the
Rigid Air Barrier to the back of the
aluminium window or door frame



Flashclad
CLADDING FOR LIFE

SILL - DOOR OR WINDOW AT FLOOR LEVEL

Original Scale 1:2

Revision - 05 August 2021

Eurobord
VERTICAL